

# ZERO8 (SE 708) - Eight Channel Trader Endpoint

## Speaker Channels

- 8 Dynamic Channels
- Rotary Volume Controls
- Multi-Colour LED status indication 'in key'
- Tap Latch and PTT modes supported
- Auto Answer for Incoming Point to Point
- Answer to handset supported
- User Programmable

## Call Types

- Hoot 'n' Holler
- Group Calls
- Answerback Calls
- Audio Distribution
- Point to Point Intercom
- Private Line Automatic Ring Down (PLAR)
- Private Line Manual Ring Down (MRD)
- Telephony<sup>1</sup>

## Intercom Functionality

- 32 Intercom Speed Dials
- Intercom Privacy
- Last Number Redial
- Directories - Corporate, Personal, Location and Group
- Intercom Call Registers - Made, Received and Missed

## Telephony Functionality

- Last Number Redial
- Telephony Call Registers - Made, Received and Missed
- Hold<sup>2</sup>
- Up to 200 Answer Bridged Call/Line Appearances

## System Management

- Managed using iManager CMS
- SNMP status monitoring

## Input Devices

- Open Microphone
- Speakerbus pluggable gooseneck microphone
  - Cardioid Microphone (52-09-021) 500mm, 8.5 Diameter
  - Close Talking Noise Cancelling Microphone (52-09-022) 550mm, 8.5 Diameter
- Handset Support (optional)
- Headset Support (optional)

## Voice Characteristics

- Voice Frequency Range 50Hz - 7KHZ
- Microphone Sensitivity 63 ± 3dB
- Loudspeaker Output 2W RMS ~73dBA @.7m

## Housing

- Black ABS/Steel

## Dimensions

- Height: 200 mm (7.87 in)
- Depth: 160 mm (5.90 in)
- Weight: 1.2KG (2.64 LB)

## Power Requirements

- PoE Class III IEEE 802.3af
- Typical: 6.49W
- Maximum: 15.4W

## Interfaces

- Network interface 10/100BASE-T Ethernet auto sensing with PoE
- Handset interface port (RJ11 Socket)

## Environmental

- Operating temperature 5°C - 35°C (41°F - 95°F)
- Relative humidity 10% - 85% RH, non condensing
- Storage environment Temperature 0°C - 60°C (32°F - 140°F), Humidity 10% - 85 % RH

## Declaration of Conformity

- EN60950-1, EN55022 and EN55024.

1. Telephony functionality is only available when connected to an iCS PBX. Voice mail and telephony directories are not available in this release.
2. Only calls placed on-hold on the SE 708 can be retrieved.



Rotary volume channel control, navigation and mode keys.



Illuminating LED indicators, home key & high resolution colour screen.



Alpha numeric keypad & fixed function keys.